



Fuel POD



Fuel POD are designed to provide safe long term fuel storage solutions which can be mobilised with ease and save re-fuelling time and money. These are ideal for the sites which have low fuel requirements or for emergency fuel usage. With a dual powered (battery and direct AC input) onboard metering system, dispensed fuel gets measured & recorded making these tankers the best solution for any industry. These can be shifted to any desired location on small pickup trucks etc.

Optionals

- Tyre mounted chassis with leaf springs, towing hook and outriggers
- Auto Retractable hose reel
- Smart Fuel System with RFID tags
- Capacitive ATG Sensor

Salient Features

- 950 L Capacity
- Unique compact modular design with smash protection, lifting lugs and fork lift pockets
- Emergency vent & pressure vacuum valves
- Hose Reel with Dispensing Nozzle
- IS specified 9 kg DCP fire extinguisher
- Pilferage proof
- Manhole provision for cleaning
- OTP enabled protection
- Real time data on MOB FOMS portal
- Possible Integration to BRP
- Provision for power backup for emergency use

Specifications

Construction

Capacity	950 L
Compartments	Single Compartment of 950 L
Tank	3.15 mm thick M.S. Plate. Tank tested at 5 psi (0.316 kg/cm ²) pressure

Specifications

Accuracy	0.5%
Delivery	40-60 ltr/min
Power Rating	0.75 kw
Noise	<80 dB (A)
Temperature	-40 C to +60 C
Power Supply	12V DC / 230V AC (Switch Over)
Suction	0.6 Bar
Min Preset	0.01 L
Totalizer	0.00 to 99999999.99 L
Connectivity	GSM / GPS / Bluetooth / USB

Hose Reel	Auto Retractable
Hose Length	10 mtr
Tank Capacity	950 L
Battery Capacity	12V / 180Ah
Battery Charger	15A, Smart Boost Protection
Data Storage	16 GB
RFID Work Range	Upto 15 mtr
Sensor IP	IP 68
L x W x H	1771 x 1100 x 1340 mm
Weight	550 kg



Warranty

All products are guaranteed against defects due to faulty workmanship or materials for twelve months from the date of purchase. This guarantee is limited to the repair or replacement of any parts found to be defective, and no other liability—expressed, implied, or contingent—is assumed.

Disclaimer

These specifications are general guidelines for product selection and can be changed for your specific requirement. Specifications are provided for convenience of reference only and may vary upon manufacturing of individual product. Recommended for captive use only and not for sale of fuel. Any commercial use at owner's risk.



Ajashy Engineering Sales Private Limited

1505-1506, Tower 4, 15th Floor, DLF Corporate Greens,

Southern Peripheral Road, Sector-74 A, Gurugram, Haryana, India - 122004

Fixed Lines: 0124-5181505/1506 | +91-9311666631 Email: info@ajashy.com Web: www.ajashy.com