



Industrial Grapple

PI



Heavy Duty Grapple

PH



Farm Grapple

PA



Farm Fork

FA



Technical Specification



Industrial grapple with low flank bucket suitable for collection of garbage, debris and for general industrial use.

2 independent hydraulically operated upper claws.

Heavy duty grapple with detachable big low spikes suitable for tough construction and farming jobs.

2 independent hydraulically operated upper claw.

Farm grapple with detachable lower spikes for



general farming works (collection of manure, hay, shrubs, etc.).

Single upper grapple with hydraulic control.






Farm fork with detachable lower spikes for general farming works (collection of manure, hay, shrubs, etc.).

Detachable lower spikes.

Farm Grapples / Farm Fork

| FARM GRAPPLE | MODEL | PA 125 | PA 140 | PA 155 | PA 168 | PA 185 | |
|---|--|----------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| FARM FORK | MODEL | FA 125 | FA 140 | FA 155 | FA 168 | FA 185 | |
| Technical specification | um | | | | | | |
| Working width | mm | 1250 | 1400 | 1550 | 1680 | 1850 | |
| Upper grapples for PA mod. | n. | 4 | | | | | |
| Lower spikes | n. | 8 | 9 | 10 | | 11 | |
| Lower spikes length | mm | 800 | | | | | |
| Weight standard configuration for PA mod. | kg | 195 | 220 | 240 | 260 | 285 | |
| Weight standard configuration for FA mod. | kg | 135 | 155 | 170 | 185 | 200 | |
|  | ton | 1,3-1,8 | 1,7-2,4 | 2,0-2,6 | 2,2-3,0 | 2,4-3,5 | |
|  | Overall size in standard configuration | A cm B cm C cm | 125 PA-74 / FA-61 90 | 140 PA-74 / FA-61 90 | 155 PA-74 / FA-61 90 | 168 PA-74 / FA-61 90 | 185 PA-74 / FA-61 90 |

Heavy Duty Grapple / Industrial Grapple

| HEAVY DUTY GRAPPLE | MODEL | PH 140 | PH 155 | PH 168 | PH 185 | PH 205 | |
|---|--|----------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| INDUSTRIAL GRAPPLE | MODEL | PI 140 | PI 155 | PI 168 | PI 185 | PI 205 | |
| Technical specification | um | | | | | | |
| Working width | mm | 1400 | 1550 | 1680 | 1850 | 2050 | |
| Upper grapples | n. | 4 | | | | | |
| Lower spikes for PH mod. | n. | 9 | 10 | 11 | 12 | 14 | |
| Lower spikes length for PH mod. | mm | 800 | | | | | |
| Weight standard configuration for PH mod. | kg | 370 | 400 | 430 | 490 | 580 | |
| Weight standard configuration for PI mod. | kg | 275 | 300 | 320 | 350 | 495 | |
|  | ton | 1,9-2,5 | 2,2-2,8 | 2,6-3,6 | 3,4-4,2 | 4,0-4,8 | |
|  | ton | 2,3-3,2 | 2,8-3,6 | 3,4-4,6 | 4,4-5,6 | 5,0-7,5 | |
|  | ton | 2,8-3,4 | 3,0-3,8 | 3,6-5,2 | 5,0-6,0 | 5,8-6,6 | |
|  | ton | – | – | – | 4,0-5,0 | 4,8-6,0 | |
|  | Overall size in standard configuration | A cm B cm C cm | 140 73 PI-79 / PH-86 | 155 73 PI-79 / PH-86 | 168 73 PI-79 / PH-86 | 185 73 PI-79 / PH-86 | 205 87 PI-90 / PH-88 |

Data, descriptions and images of this document are not binding hence GF Gordini reserves the right to alter part or all of them at any time with no notice.

ACCESSORIES FOR OPERATING MACHINES



Ajashy Engineering Sales Private Limited

1505-1506, Tower 4, 15th Floor, DLF Corporate Greens
Southern Peripheral Road, Sector - 74A, Gurgaon, Haryana - 122004
Fixed Lines: 0124 - 2663245 / 46 | Email: info@ajashy | Web:www.ajashy.com

