



Industrial Grapple

PI



Heavy Duty Grapple

PH



Farm Grapple

PA



Farm Fork

FA



Technical Specification

Industrial grapple with low flank bucket suitable for collection of garbage, debris and for general industrial use.

2 independent hydraulically operated upper claws.

Heavy duty grapple with detachable big low spikes suitable for tough construction and farming jobs.

2 independent hydraulically operated upper claw.

Farm grapple with detachable lower spikes for

general farming works (collection of manure, hay, shrubs, etc.).



Single upper grapple with hydraulic control.

Farm fork with detachable lower spikes for general farming works (collection of manure, hay, shrubs, etc.).






Detachable lower spikes.



Farm Grapples / Farm Fork

FARM GRAPPLE	MODEL	PA 125	PA 140	PA 155	PA 168	PA 185	
FARM FORK	MODEL	FA 125	FA 140	FA 155	FA 168	FA 185	
Technical specification	um						
Working width	mm	1250	1400	1550	1680	1850	
Upper grapples for PA mod.	n.	4					
Lower spikes	n.	8	9	10		11	
Lower spikes length	mm	800					
Weight standard configuration for PA mod.	kg	195	220	240	260	285	
Weight standard configuration for FA mod.	kg	135	155	170	185	200	
	ton	1,3-1,8	1,7-2,4	2,0-2,6	2,2-3,0	2,4-3,5	
	Overall size in standard configuration	A cm B cm C cm	125 PA-74 / FA-61 90	140 PA-74 / FA-61 90	155 PA-74 / FA-61 90	168 PA-74 / FA-61 90	185 PA-74 / FA-61 90

Heavy Duty Grapple / Industrial Grapple

HEAVY DUTY GRAPPLE	MODEL	PH 140	PH 155	PH 168	PH 185	PH 205	
INDUSTRIAL GRAPPLE	MODEL	PI 140	PI 155	PI 168	PI 185	PI 205	
Technical specification	um						
Working width	mm	1400	1550	1680	1850	2050	
Upper grapples	n.	4					
Lower spikes for PH mod.	n.	9	10	11	12	14	
Lower spikes length for PH mod.	mm	800					
Weight standard configuration for PH mod.	kg	370	400	430	490	580	
Weight standard configuration for PI mod.	kg	275	300	320	350	495	
	ton	1,9-2,5	2,2-2,8	2,6-3,6	3,4-4,2	4,0-4,8	
	ton	2,3-3,2	2,8-3,6	3,4-4,6	4,4-5,6	5,0-7,5	
	ton	2,8-3,4	3,0-3,8	3,6-5,2	5,0-6,0	5,8-6,6	
	ton	–	–	–	4,0-5,0	4,8-6,0	
	Overall size in standard configuration	A cm B cm C cm	140 73 PI-79 / PH-86	155 73 PI-79 / PH-86	168 73 PI-79 / PH-86	185 73 PI-79 / PH-86	205 87 PI-90 / PH-88

Data, descriptions and images of this document are not binding hence GF Gordini reserves the right to alter part or all of them at any time with no notice.

ACCESSORIES FOR OPERATING MACHINES



Ajashy Engineering Sales Private Limited

1505-1506, Tower 4, 15th Floor, DLF Corporate Greens
Southern Peripheral Road, Sector - 74A, Gurgaon, Haryana - 122004
Fixed Lines: 0124 - 2663245 / 46 | Email: info@ajashy | Web:www.ajashy.com

