



## Umbilical Reel Drives



Umbilical Reel Drives are used for spooling and unspooling of rigid and flexible pipes, umbilicals, risers and other products for offshore applications stored on reels. Our reel drive units consist of two towers, one being the drive tower & other being the idle tower which can be separately transported facilitating ease of transportation. The drive tower gets the driving power from the electrical or hydraulic motor.

### Optionals

- Electrical or Hydraulic Motor drive
- VFD (Variable Frequency Drive) panels in electrical models for precisely controlled RPMs
- Various drum and cable sizes

### Technical Specifications:

Umbilical / Hose Length	Upto 4000 mm
Capacity	Upto 100 T
Rotation	Bi-Directional
Rotary Drive	SS 304, SS 316 Stainless Steel
Hydraulic Motor	Rexroth / Bosch
Electrical Motor	Kirloskar / ABB / Crompton Greaves / Havells
Gearbox	Elecon / Omega
VFD	ABB / Yaskawa

### Warranty

All products are guaranteed against defects due to faulty workmanship or materials for twelve months from the date of purchase. This guarantee is limited to the repair or replacement of any parts found to be defective, and no other liability—expressed, implied, or contingent—is assumed.

### Disclaimer

These specifications are general guidelines for product selection and can be changed for your specific requirement. Specifications are provided for convenience of reference only and may vary upon manufacturing of individual product.