



Concrete mixer bucket



BC



Technical Specification



Concrete mixer bucket with HARDOX blades and STRENX bottom.

Interchangeable and bolded **blades**.

It loads up the loose material like a normal bucket. After mixing it downloads the concrete through the **central outlet** or by tilting the bucket.







Optimal mixing of material.

The hinged front **safety grid** can be opened to clean up interior.

Safety hydraulic valve which blocks hydraulically the mixing if the grid is open (optional).

Interchangeable and bolded **linkage plate**.

Concrete mixer bucket

MODEL		BC 250	BC 300	BC 350	BC 500	BC 700	BC 900	
Technical specification	um							
Bucket width	mm	1250	1450	1650	1650	1750	2000	
Overall width	mm	1340	1590	1790		1890	2140	
Oil flow, min-max	lt/min	25-40	30-50	35-60	60-80	80-120	120-180	
Oil pressure, min-max	bar	170-200		180-200	200-240	200-280		
Maximum capacity	lt	250	300	350	500	750	1000	
Weight, attachment only standard configuration	kg	350	380	420	500	730	850	
Total weight at maximum capacity	kg	950	1100	1260	1700	2530	3250	
Transmission		hydraulic motor and chain						
Output port control		hydraulic						
 ton		3,0-4,5	3,5-5,3	4,0-5,8	4,5-6,0	–	–	
 ton		3,0-4,0	3,5-4,5	4,0-5,5	5,0-7,0	6,5-9,0	8,5-12,0	
 ton		3,0-4,5	3,8-5,0	4,5-6,0	6,0-8,0	7,0-10,0	9,0-12,0	
 ton		5,0-7,0	6,0-8,0	7,0-9,0	7,5-10,0	8,0-11,0	10,0-15,0	
 ton		8,0-10,0	9,0-12,0	11,0-15,0	14,0-19,5	18,0-24,0	22,5-28,5	
	Overall size in standard configuration	A cm	134	159	179	179	189	214
		B cm	68	68	68	75	96	98
		C cm	81	81	81	90	103	106

Technical note for application on Skid Steer Loaders

Maximum operating weight acceptable for the machine (maximum load without standard bucket provided by the Manufacturer) must exceed the maximum mass of the mixer bucket in the conditions of maximum load technically possible (see "Overall weight and maximum capacity").



ACCESSORIES FOR OPERATING MACHINES



Ajashy Engineering Sales Private Limited

1505-1506, Tower 4, 15th Floor, DLF Corporate Greens
 Southern Peripheral Road, Sector - 74A, Gurgaon, Haryana - 122004
 Fixed Lines: 0124 - 2663245 / 46 | Email: info@ajashy | Web:www.ajashy.com

