

TFC / TFAM / TFA / TFB / TFW / TFX / TFS







Technical Specification







Excavator forestry mulcher meant to shred grass, shrub, bush and to grind standing trees and limbs.
Leveling roller to adjust cutting height.
Side support skids with replaceable runner.
Solid reinforced structure in **HARDOX** and **STRENX**.
Completely closed structure for protection.

Rotor with collapsible **swinging tools**, TFAM/ TFB versions.
 Rotor with **fixed tools** with anti wear inserts, TFA/ TFW/TFX/TFS versions.
High performances thanks to **hydraulic pistons motor** with belt transmission.

Forestry excavator mulcher

		TFC		TFAM	TFA	TFB		
MODEL		80	100	100	100	100	120	140
Technical specification	um							
Working width	mm	800	1000	1000		1000	1200	1400
Oil flow, min-max	lt/min	40-55		75-90		100-120		
Oil pressure, min-max	bar	230-250		240-260		250-300		
Weight standard configuration	kg	350-400		550	560	820	900	980
Max cutting	Ø mm	80		100		120		
Rotor	Ø mm	342		360		410		
 Collapsible swinging tools	n.			18	-	16	20	24
 Fixed tool with anti wear inserts	n.	-	-	-	37	-	-	-
 ton	ton	29	37	6,0-11,0		10,0-16,0		
 Overall size in standard configuration	A cm	100	120	120		127	147	167
	B cm	55	55	80		73	73	73
	C cm	95	95	80		92	92	92

		TFW		TFX		TFS		
MODEL		120	140	120	140	120	140	160
Technical specification	um							
Working width	mm	1200	1400	1200	1400	1200	1400	1600
Oil flow, min-max	lt/min	100-120		130-140		180-200		
Oil pressure, min-max	bar	250-300		250-310		250-300		
Weight standard configuration	kg	920	1010	1040	1170	1230	1360	1430
Max cutting	Ø mm	150		250		400		
Rotor	Ø mm	410		440		520		
 Collapsible swinging tools	n.	-	-	-	-	-	-	-
 Fixed tool with anti wear inserts	n.	30	36	30	36	30	36	42
 ton	ton	10,0-16,0		16,0-20,0		20,0-35,0		
 Overall size in standard configuration	A cm	147	167	153	173	155	175	195
	B cm	73	73	80	80	88	88	88
	C cm	105	105	105	105	112	112	112

Data, descriptions and images of this document are not binding hence GF Gordini reserves the right to alter part or all of them at any time with no notice.



Ajashy Engineering Sales Private Limited

1505-1506, Tower 4, 15th Floor, DLF Corporate Greens,
Southern Peripheral Road, Sector-74 A, Gurugram, Haryana, India - 122004

Fixed Lines: 0124-5181505/06 | +91-9311666631 Email: info@ajashy.com Web: www.ajashy.com

