



## Technical Specification



**Excavator mulcher** to top grass and mulch bushes, brambles, shrubs and underwood suitable for excavators and backhoes.




**Leveling roller** for adjustment of cutting height.

**Side skids** with replaceable runners.

**Self leveling support** with smooth plate (pin bracket for excavator on request).

**Completely closed structure** for protection. Different types of tools available (on request).

# Excavator mulcher

		TCB	TCM		TCS		TCE		TCR			
MODEL		60	60	80	80	100	90	110	95	115	125	
Technical specification	um											
Working width	mm	600	600	800	800	1000	900	1100	950	1150	1250	
Oil flow, min-max	mm	18-30	32-40		35-45		50-70		75-90			
Oil pressure, min-max	bar	180-200	180-220		180-220		200-220		200-220			
Weight standard configuration	kg	100	175	200	245	275	440	470	440	480	495	
Max cutting	Ø mm	20	30		30		40		50			
Blade	n.	10	-		-		-	-	-	-	-	
Hammer	n.	10	8	12	12	16	12	16	8	10	12	
	ton	1,5-2,5	2,5-3,5		3,5-5,5		5,5-8,0		7,0-9,0			
	ton	-	-		-		6,0-9,0		8,0-10,0			
	Overall size in standard configuration	A cm	63	90	110	95	115	90	110	115	135	145
		B cm	55	60	60	58	58	60	60	69	69	88
		C cm	65	75	75	84	84	75	75	94	94	94



Data, descriptions and images of this document are not binding hence GF Gordini reserves the right to alter part or all of them at any time with no notice.



## Ajashy Engineering Sales Private Limited

1505-1506, Tower 4, 15th Floor, DLF Corporate Greens,  
Southern Peripheral Road, Sector-74 A, Gurugram, Haryana, India - 122004

Fixed Lines: 0124-5181505/06 | +91-9311666631 Email: info@ajashy.com Web: www.ajashy.com

