

TFM / TFF



Technical Specification



Forestry mulcher to mulch shrubbery, brambles, bushes, trees and limbs.

Limbs bar.







Hydraulic cover opening for inspection and service.
Adjustable **rear roller** to set cutting height.

Side support skids with replaceable runners.

Rotor with **collapsible hinged hammers** for mod. TFM.

Rotor with **fixed tools** for mod. TFF.

Forestry mulcher

MODEL		TFM 160	TFM 180	TFF 160	TFF 180
Technical specification	um				
Working width	mm	1600	1800	1600	1800
Oil flow, min-max	lt/min	100-130		100-130	
Oil pressure, min-max	bar	200-300		200-300	
Weight standard configuration	kg	1170	1260	1230	1300
Max cutting	Ø mm	150		180	
 Collapsible swinging tools	n.	30	34	-	
 Fixed tool with anti wear inserts	n.	-		42	
 ton	ton	3,0-4,8	3,5-5,2	3,0-4,8	3,5-5,2
 ton	ton	6,0-8,5	7,0-9,5	6,0-8,5	7,0-9,5
 ton	ton	6,0-8,5	7,0-9,5	6,0-8,5	7,0-9,5
 Overall size in standard configuration	A cm B cm C cm	189 155 111	209 155 111	189 155 111	209 155 111



Data, descriptions and images of this document are not binding hence GF Gordini reserves the right to alter part or all of them at any time with no notice.



Ajashy Engineering Sales Private Limited

1505-1506, Tower 4, 15th Floor, DLF Corporate Greens,
Southern Peripheral Road, Sector-74 A, Gurugram, Haryana, India - 122004

Fixed Lines: 0124-5181505/06 | +91-9311666631 Email: info@ajashy.com Web: www.ajashy.com

